



Enhance the longevity and efficiency of your downhole equipment with the Evolution Anti-Vibration Centralizer (AVC). Specifically designed to run alongside the tubing string, this centralizer keeps the tubing centered, preventing premature wear on both the casing and tubing.

Key Benefits

- **Reduced Vibration:** Effectively minimizes harmonics and vibrations caused by the downhole PCP, extending the life of your equipment.
- **Enhanced Centralization:** Keeps the top of the PCP pump and the production string centered during installation and production, ensuring optimal performance.
- **Increased Production:** Safety allows for higher PCP pump speeds, boosting overall production rates.
- **Durability:** Features a full tubing drift and high bypass, ensuring smooth operations and reduced wear on all downhole tools.

Specifications						
Casing		Anti-Vibration Centralizer				
Size	Weight	O.D.	I.D.	Length	Connection	
in mm	lbs/ft kg/m	in mm	in mm	in mm	in mm	
5-1/2 139.7	14.0 - 20.0 20.8 - 29.8	5.22 132.6	2.50 63.5	19.00 482.6	2-7/8 EU	EUE
		5.13 130.3	3.00 76.2		3-1/2 EU	EUE
	17.0 - 26.0 25.3 - 38.7	4.96 126.0	2.50 63.5	19.00 482.6	2-7/8 EU	EUE
		6.12 155.4	2.50 63.5		2-7/8 EU	EUE
6-5/8 168.3	20.0 - 32.0 29.8 - 47.6	6.23 158.2	3.00 76.2	19.00 482.6	3-1/2 EU	EUE
		6.12 155.4	2.50 63.5		2-7/8 EU	EUE
	17.0 - 26.0 25.3 - 38.7	6.63 168.4	3.96 100.6	19.50 495.3	4-1/2 EU	EUE
			3.96 100.6		36.00 114.3	
	17.0 - 29.0 25.3 - 43.2	6.63 168.4	2.44 62.0	19.00 482.6	2-7/8 EU	EUE
			2.44 62.0		3-1/2 EU	EUE
	26.0 - 44.0 38.7 - 65.5	6.33 160.7	3.00 76.2	19.00 482.6	2-7/8 EU	EUE
			3.00 76.2		3-1/2 EU	EUE
9-5/8 244.5	32.0 - 47.0 47.6 - 69.9	9.06 230.1	3.00 76.2	19.00 482.6	3-1/2 EU	EUE
			3.96 100.6	19.50 495.3	4-1/2 EU	EUE
			3.83 97.3	21.35 542.3	4-1/2 BTC	
			3.83 97.3	21.35 542.3	4-1/2 BTC	
10-3/4 273.1	32.75 - 45.50 48.7 - 67.7	10.34 262.6	3.83 97.3	21.35 542.3	4-1/2 BTC	